9000E 5-12 kW Generator (LCD-Display)



Universal corona generator for all applications

Sophisticated electronics in a compact housing, innovative software and hardware solutions with a user-friendly interface — our high-tech generator 9000E is tailor made for the requirements of the converting industry. Reliable results, uninterrupted operation and a low overall cost of ownership are important qualities in a device that is expected to fulfil one big expectation: "install and forget".

Product features

Robustness

Sensitive electronics are safely shielded from dirt and humidity, making the generator suitable for operation under adverse climatic conditions.

Low operation costs

Fine-tuning to the resonance frequency of the system ensures maximum efficiency.

Low maintenance costs and long service life

The generator is equipped with comprehensive self-diagnostic functionality and safeguards, which contribute to reliable long-term operation.

Safe operation

The fast-acting short-circuit detection is just one of many active and passive design features protecting the operator foremost, and the system.

Intuitive user interface

The LCD display for navigation and the rotary control knob work together perfectly for time-saving and intuitive operation.



Adhesion guaranteed!

Generator 9000E (LCD-Display)

Technical features

- The European languages are members of the same family.
- The European languages are members of the same family.
- Their separate existence is a myth.
- Their separate existence is a myth.
- The European languages are members of the same family.
- The languages only differ in their grammar, their pronunciation and their most common words.
- The languages only differ in their grammar.
- Their separate existence is a myth.
- Early detection and alarm of deviation from standard (voltage, current, temperature).
- The languages only differ in their grammar, their pronunciation and their most common words.
- The languages only differ in their grammar, their pronunciation and their most common words.
- Their separate existence is a myth.

Options

The quick, brown fox jumps over a lazy dog. DJs flock by when MTV ax quiz prog. Junk MTV quiz graced by fox whelps. Bawds jog, flick quartz, vex nymphs. Waltz, bad nymph.

The quick, brown fox jumps over a lazy dog. DJs flock by when MTV ax quiz prog. Junk MTV quiz graced by fox whelps.

Technichal data

Treatment power	5 – 12 kW
Output Frequency	15 – 35 kHz
Mains Voltage	3 x 380 – 480 V, +/– 10%, 50/60 Hz
Protection	IP43
Dimensions (WxHxD)	780 x 600 x 350 mm
Weight	approx. 60 kg
Colour	RAL 7035, light grey, structured
Ambient temperature	max. 40 °C (without optional cooling)



Improved dyeing

Improved adhesion

SOFTAL Ouality



Low operating cost



Custom-engineered solutions



No more wet chemicals

High wettability

Environmentally friendly

process



Uninterrupted operation

